



## LED B10 Filament

**4W = 40W Incandescent  
Candelabra**



Product Description		LE-4B10
Body Size	L (mm)	97 ± 2
	D (mm)	32 ± 2
LED QTY (pcs)		4
LED Source		Epistar
Dimmable		Y
Input Voltage (V)		120V
Power (W)		4W
Luminous Flux		240-350LM
SDCM		<4
CRI		>80
Power Factor		>0.9
Life time (HRS)		15,000

Product Code	Description	CCT	Volts	Watts	Base	Lumens	Note
80040	LE-4B10/IF/WW	2700K	120V	4W	E12/E26	350	Frosted, =40W
80036	LE-4B10/CL/WW	3000K	120V	3W	E12/E26	240	equivalent to 25W
80037	LE-4B10/CL/WW	3000K	120V	4W	E14	350	European Base, =40W
80038	LE-4B10/CL/30	3000K	120V	5W	E12/E26	300	equivalent to 40W
84036	LE-4B10/CL/CW	5000K	120V	4W	E14	350	European Base, =40W
84037	LE-4B10/CL/WW	3000K	120V	4W	E26	350	equivalent to 40W

**Disclaimer:**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



**AW LIGHTING**  
[www.awlight.com](http://www.awlight.com)